


# F503

## Flame-retardant Tissue Paper Double Sided Tape



### Composition:



Flame-retardant Acrylic Adhesive  
Tissue Paper  
Flame-retardant Acrylic Adhesive  
Release Liner

### Applications:

- Punching, bonding of nameplates, membrane switch and automobile accessories with fireproof requirements.
- Interior materials for automobiles, train cars and airplanes.
- For various foam materials such as PU, PE, EPDM, PET.

### Features:

- UL94 VTM-0 certified.
- Superior initial adhesion.
- Excellent adhesion to rough surfaces.
- Excellent performance under a wide range of temperature condition.
- Low smoke, non-toxic, low burning rate and no dripping during burning.

### Standard Size


• Total Thickness (without release paper)	0.12mm
• Liner thickness	0.11mm
• Width	10mm-1020mm
• Length	50m-500m

## Technical Data (average values)

• Backing material	Tissue paper
• Color	White
• Type of adhesive	Acrylic Pressure Sensitive Adhesive
• Temperature resistance range	-20°C-60°C
• Temperature resistance short term	100°C
• Temperature resistance long term	60°C
• Loop tack	≥26#
• Holding power	Up to 180°C for 120 min.

180 Degrees of Peeling Adhesion	
Substrate	Avg. Test Values
Stainless Steel	16N/25mm
ABS	15 N/25mm
PC	20 N/25mm
PE	4 N/25mm
PVC	17 N/25mm
PP	10 N/25mm

Unit:N/25mm  
Sample Width:25mm  
Backing Material: PET film  
Application Condition:  
3 pass back and forth with a  
2.5kg roller  
Peeling Speed: 300mm/min  
Peeling Angle: 180 degree  
Measurement Temperature:  
23 °C/65%RH



### Storage:

1. To obtain optimal adhesion, the bonding surface must be dry and clean.
2. The ideal application temperature range is 20°C to 40°C. To apply tape on surface at temperature below 10°C be not recommend, because the adhesive becomes firm to adhere lightly.

**Test Method:** In accordance with GB/T 4851-1998 method.

### Shelf Life:

12 months when stored in original carton at 23°C and 65% relative humidity

### Other:

- Rewinding length commonly used: 55m /roll, and can be processed according to customer demand
- Special carton packaging