

FRJ150

Masking Tape



Composition:



Nature Rubber Adhesive
Crepe Paper

Applications:

- Indoor decoration.
- Paint masking.
- General masking applications.

Features:

- Instant adhesion to a variety of surfaces.
- Good paint hold-out and bleed-through resistance.
- High temperatures resistant of 80°C.

Standard Size

• Total Thickness	0.15mm±0.015mm
• Width	10mm-850mm
• Length	50m-500m

Technical Data (average values)

• Backing material	Crepe Paper
• Color	Beige
• Type of adhesive	Nature Rubber Adhesive
• Temperature resistance range	-10°C-80°C

• Holding Power	>3±1 Hrs
• Loop tack	≥18#
• Elongation	11±1%
• Adhesive strength	4.5-5.5N/25mm
• Tensile strength	60-65N/25mm

Application Properties:

1. To obtain optimal adhesion, the bonding surface must be dry and clean.
2. The ideal application temperature range is 20°C to 40 °C. To apply tape on surface at temperature below 10°C be not recommend, because the adhesive becomes firm to adhere lightly.

Test Method: In accordance with GB/T 4851-1998 method.

Shelf Life:

12 months when stored in original carton at 23°C and 65% relative humidity.

Other:

- Rewinding length commonly used: 55m /roll, and can be processed according to customer demand
- Special carton packaging.