


F003 Water Purifier Tape



Composition:



Synthetic Rubber
Ro Film

Applications:

- Excellent quality filters for RO system.

Features:

- Abrasion resistance & Cold resistance.
- Strong holding power and excellent adhesion.
- Environmentally friendly waterproof and acid resistant adhesive.

Technical Data (Average Values)

• Backing material	RO Film
• Thickness	0.085mm
• Color	Blue
• Type of adhesive	Synthetic Rubber
• Width	10mm~1240mm
• Length	50m~2500m
• Holding power	≥24h
• Loop tack	≥15#
180° Peel Adhesion	6.5N/25mm

Storage:

- Please be sure to keep the tape in its box when not using.
- The ideal application temperature range is 20°C to 40°C.
- Keep in a cool and dark place away from direct sunlight.

Test Method:

In accordance with GB/T 4851-1998 method.

Shelf Life:

12 months when stored in original carton at 23° C and 65% relative humidity.

Note:

- Remove all oil, moisture and dirt from the surface of the substrate before applying.
- Make sure the product is suitable for the application (objective and conditions) before attempting to use.

DISCLAIMER

- The above information is believed to be reliable and accurate but is presented without a guarantee on our part.
- F6 Adhesive Tape gives no warranty as to the fitness of the above product for any particular purpose and any implied warranty or condition statutory or otherwise.
- It is recommended to make a trial before any bulk usage.
- Use in combination with another method of joining if there is possibility of an accident.

Dahai office building ,
No.499 Taikang middle road, Yinzhou District ,
Ningbo City ,Zhejiang Province ,China .

Tel. +86 18606581882
Fax. +0574-88913422
shakira@f6adhesive.com
<https://www.f6adhesive.com/>

